



TSE/O



TSE/2



TSE/3

 **Serratura Elettronica Digitale**

- Spessori: della porta 4 mm. - del corpo 2 mm.
- Serratura elettromagnetica con codice cambiabile.
- Segnalazioni sonore e visibili (led e buzzer) per conferma digitazione ed errori.
- Serratura a chiave per apertura di emergenza (2 chiavi fornite).
- Funzionamento con 4 batterie alcaline da 1,5 V.
- Tappetino sulla base.
- Fori di ancoraggio sulla base e sullo schienale (2+2).
- Tasselli per fissaggio in dotazione.
- Verniciatura a polvere termoindurente colore grigio chiaro.

 **Digital Combination Lock**

- Thickness: of door 4 mm. - of body 2 mm.
- Electromagnetic lock with changeable code.
- Acoustic and visual signals to confirm code and errors by means of buzzer and led.
- Override key for emergency opening (2 keys supplied).
- Powered by 4 x 1,5 V alkaline batteries.
- Internal carpet provided.
- Base and back fixing holes (2+2).
- Screw anchor fixing bolts provided.
- Light grey colour powder coated finishing.



Art Code	Misure esterne mm.			Misure interne mm.			Dim. porta mm.		Numero catenacci Number of bolts	Peso Weight	Litri Volume
	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W			
<b>TSE/O</b>	200	310	200	190	300	150	160	270	2	7,5	9,5
<b>TSE/2</b>	250	350	250	240	340	186	210	310	2	10,5	17
<b>TSE/3</b>	400	350	250	390	340	186	360	310	2	13,5	25